


Features

- LGA 1700 socket supports 12th/13th/14th Gen Intel® Core™ i9/7/5/3 Processor, codenamed Alder Lake/Raptor Lake/Raptor Lake Refresh
- Intel® Integrated UHD Graphic with Xe Architecture (CPU Dependent)
- Intel® R680E PCH
- 4 x DIMM up to 128GB Max Dual Channel DDR5 5600MHz with ECC Support
- 2 x Intel® I225-LM 2.5GbE
- 1 x Gen 5 PCIe x16, 2 x Gen 4 PCIe x4, 1 x Gen 3 PCIe x4, 1 x Gen3 PCIe x1, 2 x Gen 3 PCIe x1 Open End
- 2 x M.2 M-Key NVMe, 1 x M.2 E-Key supports CNVi
- TPM 2.0, Intel® AMT 16
- x8 Gen4 DMI
- Supports 4 Independent Display: 2 x HDMI, 2 x DP++
- 6 x COM, 4 x SATA III
- 8 x USB 3.2 Gen 2, 8 x USB 2.0, 1 x USB 3.2 Gen 2x2 Type-C
- I²C, SMBus, PS/2, LPT, 8-bit GPIO
- Supports Win 10, Win 11, Linux



Specifications

System	
CPU	LGA1700 Socket supports 12th Gen Alder Lake/ 13th Gen Raptor Lake/ 14th Gen Raptor Lake Refresh Intel® Core™ i9/7/5/3, Pentium, Celeron Processor up to 16 Cores 24 Threads Hybrid
Chipset	Intel® R680E PCH
System Memory	4 x DIMM slots support Dual Channel DDR5 memory speed up to 5600MHz with UDIMM, up to 128GB, with ECC support
BIOS	AMI® 256Mb SPI BIOS
DMI	x8 Gen4 DMI
Expansion	1 x Gen 5 PCIe x16 (x16 Physical Black) 2 x Gen 4 PCIe x4 (x16 Physical Orange) 1 x Gen 3 PCIe x4 (x16 Physical Yellow) 1 x Gen 3 PCIe x1 (x16 Physical Yellow) 2 x Gen 3 PCIe x1 Open Ended 1 x M.2 M-Key 2242/2280/22110 NVMe (PCIe x4 + SATA III) 1 x M.2 M-Key 2242/2280/22110 NVMe (PCIe x4 Only) 1 x M.2 E-Key 2230 with CNVi Support (PCIe x1 + USB 2.0)
Watchdog Timer	Reset: 1 sec. ~ 255min. and 1sec. or 1min./step
H/W Status Monitor	Monitoring System Temperature, Voltage, with Auto Throttling Control
TPM	TPM 2.0
Intel® AMT	Intel® AMT 16
Supported OS	Windows 10, Windows 11, Linux
Display	
Chipset	Intel® Integrated UHD Graphic with Xe Architecture (CPU Dependent)
Interface	2 x HDMI 2.0b 4K@60Hz 2 x Dual Mode DisplayPort 1.4a 4K@60Hz
Multi-Display	Supports 4 Independent Displays
Audio	
Audio Codec	Realtek HD Audio Codec
Amplifier	6W Per Channel Amplifier

Ethernet

LAN 1	Intel® I225-LM 2.5 Gigabit Ethernet Controller
LAN 2	Intel® I225-LM 2.5 Gigabit Ethernet Controller

External I/O

Display	2 x HDMI 2 x DP++
USB	6 x USB 3.2 Gen 2x1 1 x USB 3.2 Gen 2x2 Type-C
LAN	2 x RJ45
Audio	Line-out, Mic-in

Internal I/O

USB	4 x USB 2.0 Headers (8 Ports) 1 x USB 3.2 Gen 2 (2 Ports)
COM	5 x RS-232 Headers 1 x RS-232/422/485 Header
SATA	4 x SATA III
PS/2	1 x PS/2
I²C	1 x I²C Header
SMBus	1 x SMBus Header
SPI	1 x SPI Header
Other	Front Audio, Front Panel, Amplifier, 8-bit GPIO

Mechanical & Environment

Power Type	AT/ATX
Power Connector	1 x 24-pin ATX Connector 1 x 8-pin ATX 12V Connector
Operating Temp.	0 ~ 60°C (32 ~ 140°F)
Storage Temp.	-20 ~ 80°C (-4 ~ 176°F)
Op Humidity	5% to 90% non-condensing
Certification Information	CE, FCC Class B, RoHS Compliant
Dimensions	12" x 9.6" (305 x 244mm)
Weight	1.85 lbs

Ordering Info

BC680R	P/N: 71832. Intel® R680E ATX Motherboard
Accessory Included	1 x I/O Shield
183000000006	2.00mm pitch 12" length serial cable
182437200040	2.54mm pitch 14" length dual port USB 2.0 cable w/ full height bracket
182000000073	2.00mm pitch 19.7" length dual port serial cable w/ full height bracket

* All product specifications and images are subject to change without notice. Last update: 03/12/2024



BCM Advanced Research
11 Chrysler, Irvine, CA 92618 USA
An Industry Leader in Industrial Motherboards &
Embedded Computing

www.bcmcom.com
BCMSales@bcmcom.com
(949) 470-1888