

Features

- Motherboard Inside: MX3350N mini ITX
- Intel N3350 Dual Core SoC Processor Onboard 2.40 GHz Max Speed
- Supports two DDR3L SoDIMM 1600 MHz system memory up to 8GB
- Supports Three Independent Displays (see detail below)
- 1 x DP++, 2 x HDMI
- 2 x M.2 sockets, 1 x PCIe x1
- 1 x COM Ports
- 4 x USB 3.0
- 12V DC-in
- TPM 2.0
- Supported OS: Microsoft Windows 10 64-bit



Specifications

System	
CPU	Intel® N3350 2-Core Processor Onboard 2.40 GHz (Max Speed)
System Chipset	SoC
BIOS	AMI® 128Mb SPI BIOS
System Memory	Two 204-pin SoDIMM DDR3L 1600MHz Up to 8 GB
Video	Intel® Integrated HD Graphic Engine
Audio Codec	Realtek HD Audio support 7.1 channel sound playback
Ethernet	Intel® I211-AT PCIe Gigabit LAN Controller Intel® I211-AT PCIe Gigabit LAN Controller
Expansion	1 x 2230 M.2 E Key (with PCIe x1 Channel & USB Signal) 1 x 2280 & 2242 M.2 M Key (with PCIe x2, & SATA III Signal)
System Fan	1 x 60mm
System Indicator	1 x Power LED, 1 x HDD LED
Storage	1 x 2.5" Drive Bay
External I/O	
Audio	1 x Mic-in and 1 x Line-out
LAN	2 x RJ-45
Display Interface	1 x DisplayPort (supports DP++) 2 x HDMI
USB	4 x USB 3.0 (Blue)
COM	1 x RS-232
Power Input	1 x DC-in

Mechanical and Environment	
Power Type	12V DC
Adapter	Input: 100 ~ 240V / 50 ~ 60Hz Output: 60W Adapter (12V @ 5A)
Operating Temperature	0 ~ 40°C (32 ~ 104°F)
Storage Temperature	-20 ~ 60°C (-4 ~ 140°F)
Operating Humidity	10 ~ 86%, non-condensing
Dimension	7.087" L x 8.00" W x 2.507" H (180.00mm L x 203.20mm W x 63.68mm H)
Certification Information	CE, FCC Class A
Weight	3.14 lbs

* All product specifications and images are subject to change without notice. Last update: 2021/04/20



BCM Advanced Research

11 Chrysler, Irvine, CA 92618 USA
An industry leader in industrial motherboards & embedded computing

www.bcmcom.com

BCMSales@bcmcom.com
(949) 470-1888