

Features

- Socket H2 LGA1155 supports the 22nm/32nm Intel® Core™ i7/i5/i3 processors with integrated graphics
- Intel® Q67 Chipset PCH platform
- Supports up to 32 GB 1066/1333 MHz DDR3 system memory
- Dual display: DVI-D, VGA, HDMI, 18/24-bit LVDS
- LVDS Connector Onboard
- 1 x PCIe x16, 1 x PCIe x4, 2 x PCI slots
- 2 x SATA III (6.0 Gb/s), 3 x SATA II (3.0 Gb/s)
- 1 x eSATA
- LPT Onboard
- 14 x USB
- 4 x COM
- Intel® Active Management Technology 7.0
- TPM 1.2

Specification

System

| | |
|---------------------|---|
| CPU | Socket H2 LGA 1155 supports 22nm/32nm Intel® Core™ i7, Core™ i5, Core™ i3 processors |
| Chipsets | Intel® Q67 Chipset PCH |
| System Memory | Four 240-pin DIMM slots support up to 32 GB dual channel 1066/1333 MHz DDR3 SDRAM memory modules |
| BIOS | AMI 32 Mb SPI BIOS |
| Expansion Interface | 1 x PCI Express x16 Slot 1 x PCI Express x4 (x16 Physical Slot) 2 x PCI Slots |
| iAMT | Intel® Active Management Technology 7.0 |
| TPM | Supported by Infineon SLB9635TT 1.2 |
| Watchdog Timer | Reset: 1 sec.~255 min. and 1 sec. or 1 min./step |
| H/W Status Monitor | Monitoring CPU temperature, voltage, and cooling fan status. Auto throttling control when CPU overheats |

Display


| | |
|----------------|----------------------------|
| Chipset | Intel® Integrated Graphics |
| Display Output | HDMI, DVI-D, VGA and LVDS |

Back I/O Panel

| | |
|---------------|--|
| KB/MS | 2 x PS/2 Connectors |
| Display Port | 1 x DB-15, 1 x DVI-D, 1 x HDMI |
| LAN and USB | 2 x Stack up RJ45 and USB (4 USB) |
| eSATA and USB | 1 x Stack up eSATA and USB Connector (2 USB) |
| Audio | 1 x 3-Jacks Audio |

Onboard I/O Headers

| | |
|------|--|
| MIO | 1 x LPT, 1 x Front Audio, 1 x Amplifier Header, 1 x Front Panel Header, 1 x 4-pin CPU Fan Header, 2 x 4-Pin-Chassis Fan Header |
| USB | 4 x USB 2.0 (8 Ports) |
| COM | 4 x RS-232 |
| SATA | 3 x SATA II (3.0 Gb/s), 2 x SATA III (6.0 Gb/s) |
| LVDS | 1 x 18/24-bit Dual Channel LVDS |
| GPIO | 1 x 8-bit GPIO |



Audio

| | |
|-----------------|----------------------------------|
| AC'97 Codec | Realtek® ALC892 HD Audio Codec |
| Audio Interface | Line-out, Line-in, Mic-in, SPDIF |

Ethernet

| | |
|-------|-------------------------------------|
| LAN 1 | Intel® 82579LM PHY Gigabit Ethernet |
| LAN 2 | Intel® 82574L PCIe Gigabit Ethernet |

Mechanical and Environment

| | |
|-----------------------|--|
| Power Type | ATX |
| Operating Temperature | 0° C to 60° C |
| Storage Temperature | -20° C to 80° |
| Operating Humidity | 5%~90% relative humidity, non-condensing |
| Form Factor | Micro ATX |
| Dimensions | 9.6" (L) x 9.6" (W) |
| Weight | 1.45 lbs |

Ordering Information

* OEM products are designed for OEMs with ongoing and consistent order requirements and subject to minimum order quantities. Evaluation units are available without such restrictions. BCM has multiple stocking distributors that may be able to work with OEMs to streamline product deliveries. Please contact BCM Sales for

RX67QV

Intel Q67 Micro ATX Motheboard w/ LVDS connector onboard

Accessories Included

2 x SATA Cables, 1 x I/O Shield, 1 x Driver CD (Manual/Drivers), 1 x User's Quick Start Card

* All product specifications are subject to change without notice. Last update: 10/4/2013